

## Analog input 560AIR02 RTU560 product line



### Analog input, 8 channels

- AD converter resolution: 16 bit
- Measuring ranges: +/-2 mA; +/-5 mA; +/-10 mA; +/-20 mA; +/-40 mA

#### Application

The 560AIR02 module records up to 8 analog measured values.

The module 560AIR02 is able to process the following types of signals:

- Analog measured values (AMI)
- Measured floating point information (MFI)

Following measurement ranges can be configured:

- $\pm 2$  mA
- $\pm 5$  mA
- $\pm 10$  mA
- $\pm 20$  mA
- $\pm 40$  mA

Other effective ranges and live zero signals become generated out of these ranges through conversion of the communication unit (CMU).

#### Characteristics

##### Analog inputs

Basic signal checks and cyclic processing functions are already be done locally in order to unburden the communication unit. The module transmits relevant changes as event via the RTU I/O bus.

The 8 differential inputs are not galvanic isolated against the power supply.

Single-ended or differential input values are resolved by up to 4096 steps (12 bit plus sign) for 100 % measurement amplitude.

The differential inputs are protected against static and dynamic over-voltages by a protection circuit. A low-pass filter suppresses unwanted frequency components.

The internal high resolution of the AD converter (16 bit) allows to scan all measuring ranges with the same resolution. An additional measurement channel is used for automatic zero calibration. This compensates the longterm drift of the components.

For elimination of tolerances a calibration is done during production.

The synchronization of the scan cycle with the line frequency is used to increase the line frequency interference suppression of the DC input signal.

Frequency	Conversion time per channel	Scan cycle time (same for all channels)
60 Hz	54 ms	486 ms

Frequency	Conversion time per channel	Scan cycle time (same for all channels)
50 Hz	54 ms	486 ms
16.7 Hz	155 ms	1395 ms

#### **Power supply input**

The required power for the module is supplied via the RTU560 backplane.

#### **I/O controller (IOC)**

The micro-controller on the module processes all time critical tasks of the parameterized processing functions. Moreover it carries out the interactive communication with the RTU I/O bus. All configuration data and processing parameters are loaded by the communication unit via the RTU I/O bus.

The module is equipped with a serial interface to the RTU560 I/O bus on the backplane.

The analog input unit can execute the following processing functions on the measured values:

- Scan cycle and line frequency interference suppression
- Zero value supervision and switching detection
- Smoothing
- Threshold value monitoring on absolute value or with accumulation
- Periodic transmission and background cycles

During initialization and operation the module carries out a number of tests. If a fault occurs it is reported to the communication unit. All fault conditions impairing the function of the module are displayed as common fault signal by a red LED. A failure of the module is detected by the communication unit.

## Technical data

In addition to the RTU500 series general technical data, the following applies:

<b>Analog input channels 560AIR02</b>	
Inputs	8 differential inputs
Configurable measuring range	<ul style="list-style-type: none"><li>± 2 mA</li><li>± 5 mA</li><li>± 10 mA</li><li>± 20 mA</li><li>± 40 mA</li></ul>
Input impedance	50 Ω @ ±2 mA and ±5 mA, ±10 mA, ±20 and ±40 mA
Max. load	80 mA continuous @ ±10, ±20 and ±40 mA, 2 mA and 5 mA
Resolution	12 bit + sign 11 bit + sign @ ±2 V DC
AD converter resolution	16 bit
Accuracy at 25 °C	≤ 0.1 %
Linearity error at 25 °C	≤ 0.1 %
Temperature drift	≤ 100 ppm/K (0... 70 °C)
Max. common mode input voltage	±150 V DC (electrical limit) ±8 V DC (functional limit)
Max. differential input voltage	± 4 V DC (current input)
Common mode rejection	> 70 dB @ 25 °C > 60 dB @ 0... 25 °C
Configurable line frequency $f_N$	<ul style="list-style-type: none"><li>16.7 Hz</li><li>50 Hz</li><li>60 Hz</li></ul>
Line frequency interference suppression	> 100 dB @ $f_N \pm 2\%$ > 45 dB @ $f_N \pm 10\%$

## Current consumption for power supplied via RTU560 backplane

5 V DC	75 mA
24 V DC	--

## Signaling by LEDs

ERR (red)	Common fault information for the module
-----------	---

## Mechanical layout

Dimensions	160 mm x 100 mm, 3HE euro card format 4R (20 mm) front panel
Housing type	Printed circuit board
Mounting	for mounting in RTU560 racks
Weight	0.3 kg

## Connection type

RTU560 backplane connector	48 pole type F DIN 41612
----------------------------	--------------------------

## Immunity test

Electrostatic discharge IEC 61000-4-2	8 kV air / 6 kV contact (level 3) Performance criteria A
Radiated radio-frequency Electromagnetic field IEC 61000-4-3	10 V/m (level 3) Performance criteria A
Electrical fast transient / Burst IEC 61000-4-4	4 kV (level 4) Performance criteria A
Surge IEC 61000-4-5	4 kV (level 4) Performance criteria A
Conducted disturbances, induced by radio-frequency fields IEC 61000-4-6	10 V (level 3) Performance criteria A

## Environmental conditions - climatic

Operating temperature EN 60068-2-14	-25 °C ... 70 °C
Start up EN 60068-2-1	-40 °C
Max. operating temperature, max. 96h EN 60068-2-2	+85 °C
Relative humidity EN 60068-2-30	5 ... 95 % (non condensing)

## Ordering information

560AIR02 R0001	1KGT037500R0001
----------------	-----------------

ABB Power Grids Germany AG

P.O. Box 10 03 51  
68128 Mannheim, Germany

[hitachiabb-powergrids.com/rtu](http://hitachiabb-powergrids.com/rtu)

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. Hitachi ABB Power Grids does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of Hitachi ABB Power Grids.  
© 2020 Hitachi Power Grids  
All rights reserved

ABB is a registered trademark of ABB Asea Brown Boveri Ltd. Manufactured by/ for a Hitachi Power Grids company.